

EXPOSURE TO FLOODING OF COMMUNITIES ALONG EPIE CREEK IN YENAGOA METROPOLIS OF BAYELSA STATE, NIGERIA

¹Wolisi, I.H.N and, E.A. ²Obiene

1. Department of Flood & Erosion Control, Bayelsa State Ministry of Environment
Ibebiwaruwolisi068@gmail.com. (08068835076)
2. Department of Geography, Bayelsa State College of Education,
Sagbama. Obiene01@gmail.com. (08037881968)

Abstract

The study on the exposure to flooding of communities along the Epie Creek in Yenagoa Local Government Area of Bayelsa State was investigated. The study considered some physical factors which can expose inhabitants of an area to flooding. Hence, data on flood height reached on buildings and the elevation above MSL as well as the spatial variation in the dimension of flood waters around residential houses with reference to the stream channel (Epie Creek) was evaluated using inferential and descriptive statistics. The results of the analyses showed that areas within Ekeki, Amarata and Onopa are more at risk of flooding due to the height of flood waters reached on buildings. But the results of the elevation of the area slightly differs as areas within Yenezue-Epie-Okaka and Etegwe-Okutukutu are found to be relatively lower (9.5m) than other areas and are expected to be more vulnerable to flooding. Thus, there was no significant correlation between flood height and the elevation of the area above MSL. Hence, the flood height reached on buildings at different location is not directly caused by elevation. On the flood dimension in the area, the study revealed that 'proximity' is a major factor that exposes the inhabitants of Epie Creek to flooding especially for those whose dwellings are located close to the Creek. Hence, the study recommends the total relocation of people living very close to the Epie Creek to allow for better planning of the area.

Keywords: Risk, Vulnerable, Proximity, Expose, Flooding.

1.0 INTRODUCTION

Flood is a common natural disaster which can occur anywhere with associated hazard which is mostly endemic where water flows such as along the banks of rivers, lakes and other forms of water flow. Epie communities situated along the Epie Creek in Yenagoa town have been experiencing flooding in recent times during the raining season. The flood usually causes environmental havoc to lives and properties. The flooding menace in this area destroys farms, damage properties, displaces residents from the homes and sometimes causes death.

Flood as a natural disaster has been described to occur when the volume of flowing water along a defined path such as river channel, exceeds its confinement thereby overflowing the banks to cover the adjacent lands (Digha&Obiene, 2012). Hence, Liao (2012) described flood as natural hazards which possess challenges to towns and cities located along rivers. The scholar went further to state that despite the fact that most cities in developed cities like Bangkok, Thailand,

New Orleans, e.t.c, have built strong flood protection structures but are yet to escape from the effects of the hazard due to their location.

Umeuduji (2017), reported that it is obvious that people living close to source of water (such as rivers and lakes) are mostly at risk to flooding despite the lots of opportunities opened to those that inhabits such environment. Thus, it is expedient that those who live close to rivers to prepare to adapt to flood hazard. But studies have revealed that hazard is contextual. That is to say, it differs from place to place and even within a particular environment; the vulnerability of people differs from one point to another point, depending on the capacity of those who are exposed to the hazard (Kelman, 2007; Adelekan, 2010).

Vulnerability has been defined as the degree to which a system (or part of it) reacts adversely to the occurrence of a hazardous event (Proag, 2014). The term has also been viewed to mean the propensity (ability/capacity) of an exposed element such as human beings; their livelihood(s) and assets to suffer adverse effects when impacted upon by hazardous event (Cardona, et al, 2012). Thus, from the definitions above, it is obvious that, an element or a system can be vulnerable to a particular hazard when its capacity or ability to cope with the hazard is not enough and thereby resulting to a collapse of the system. Lungrenand Johnson (2012), described the term 'vulnerability' to mean the capacity of the elements or are unequally distributed in the environment.

Viewing in the perspective of the above explanations, one can comfortably state that, vulnerability is a measure of a system's ability or capacity to anticipate the presence of a hazard (potential disaster), ability to cope with the hazard when disaster strikes and; the ability or capacity to recover or recuperates from the effect(s) of the disaster. Therefore, once a system's ability to anticipate or predict potential disaster is high, it would enable it prepare to withstand the effects that may arise.

It is worthy to note that man cannot be completely free from one form of a hazard or the other because; every location on the earth's surface has a unique type of hazard that may pose difficulties within that environment. For instance, those living in mountainous areas are mostly exposed to landslides and other erosion effects. Those living close to the seashores are exposed to ocean surge, tsunami, and hurricane and so on. In the same way, those who live within floodplains of rivers are exposed to flooding and other erosion and depositional effects.

People's vulnerability to hazard have been said to differ from person to person and from location to location which depends on the 'resilience' of the people being affected. Thus, the resilience of a system has been defined as the measures adopted by the system to enable it adapt or survive in the hazard prone area. According to Adelekan, (2010) vulnerability indicators to flood hazards can be grouped into; (i) physical rainfall characteristics, landscape of the area, etc.; (ii) Social/economic (income level, land-use, resident type, etc.), (iii) resilience preparedness, coping/recovery ability etc.

Most studies have focused on the various indicators of vulnerability e.g(Digha&Obiene, 2009; Kenji, 2004; Efobi& Christopher, 2013; Collins, 2014), but much attention has not been given to the contributions of the physical landscape and the proximity of peoples' residence to the source of water. Thus, the aim of this study is to identify those physical factors that exposes the communities situated along Epie Creek to flooding and the flooding vulnerability of these communities.

2.0 METHODOLOGY

2.1 The study Area

The study area comprises communities along Epie Creek which is located within the Yenagoa Metropolis. The area is situated between Latitude $4^{\circ} 50'N$ to $5^{\circ} 05'N$ and $6^{\circ} 15'E$ to $6^{\circ} 30'E$ (Izonfuo&Bariweni, 2001). The Epie Creek is drained partly by the Orashi River and the Tailor Creek. The Epie Creek flows across 16 communities and empties into the Ekole River. Historically, like other bigger towns and cities worldwide, all the communities of Epie descent are located linearly along this channel (Epie Creek). Before now, the major occupation of the people in the area was farming and fishing due to the presence of water and the fertile lands adjacent to the stream channel. Because of the annual flooding usually experienced in the area, major crops cultivated in the area include; cassava, water yam, cocoyam, maize and vegetables.

Just like other areas within the central Niger Delta of Nigeria, the study area is flood prone due to the presence of the river channel (Epie Creek) and its tributaries. The tributaries of Epie Creek are found to connect the back-swamps which are located a few distances from the main channel.

The geomorphology of the study area is naturally sculptured to drain excess water from the strip of land inhabited by the people (which is not normally submerged by water) thereby keeping it safe from being flooded. Hence, all those who first occupied this area were relatively safe from the effects of flood. This remained the situation of the area until few years after the creation of Bayelsa state when development started creeping into the deep swamps due to urbanization. Today, urbanization has encroached major parts of the back-swamps thereby disconnecting the link between the natural reservoirs and the main stream channel (Epie Creek). This situation couple with other urbanization challenges has led to the silting of the main trunk which has exacerbated the flood situation of the area. The Map of the study area is presented in Fig, 2.1.




Fig. 2.1: Map Showing Communities along Epie Creek

2.2 Data Collection

Since Vulnerability is contextual, this study has carried out investigation on the level of vulnerability at different location taken reference from the main stream channel. The study focused on the flood extent and depth at the different location and how the inhabitants are able to cope with the effect of floods during and after the event. This was investigated through careful observation and the use of a well structured questionnaire design to sample opinion from 857 inhabitants covering the 16 communities across the study area.

2.3 Data analysis

Data collected were analyzed by means of product moment correlation technique whereby product moment coefficient (r_{xy}) was evaluated. By this, data on the flood height reached on buildings during the 2022 flood and that of elevation of the area above Mean Sea Level (MSL) were correlated. (r_{xy}). This was carried out by adopting the formula suggested in Aguwa and Onyenaobiya (2014) as presented in equation 1;

$$r_{xy} = \frac{n\sum XY - (\sum X)(\sum Y)}{\sqrt{\{n\sum X^2 - (\sum X)^2\}\{n\sum Y^2 - (\sum Y)^2\}}} \quad 1.$$

(Where; X =Height of flood reached on buildings, and Y =Elevation of the area)

3.0 RESULTS AND DISCUSSIONS

3.1 Results

The results of the determination of the height of flood water on buildings during the 2022 flood and ground level elevation above sea level in the study area are presented in Table 3.1. It shows that the flood height ranges between 1.6m and 3.2m. While MSL in the area range between 9.50M and 13M

Table 3.1: Flood Height Reached on Buildings and Elevation above MSL of Communities along Epie Creek

Community	Igbogene/Yenegwe	Akenfa/Agudama	Akenpai/Edepie	Etegwe/Okutukutu	Opolo/Biogbolo	Yenezuegene/Kpansia	Yenezue-Epie/Okaka	Ekeki/Onopa
Flood height on building (m)	2.01	2.15	2.18	1.62	2.82	2.20	2.28	3.16
Elevation above MSL (m)	13.00	12.00	10.50	9.50	11.50	10.50	9.50	10.60

(Source: Author's Fieldwork, 2024)

Height of flood water on buildings during the 2022 is further presented graphically in Figure 3.1 for a better scientific illustration and understanding




Figure3.1 Flood Height Reached on Buildings in Communities along Epie Creek During 2022 Flood (Author's Fieldwork).

The ground level Elevation above mean sea level of Communities located along the Epie Creek is presented graphically in Figure 3.2. It shows that the area stands between 9m and 12m above MSL. The areas within Yenezue-Epie-Okaka and Etegwe-Okutukutu are found to be relatively lower (9.5m) than areas within Igbogene-Yenegwe which have above mean sea level of (13m),




Figure 3.2: Elevation above mean sea level of Communities located along Epie Creek.

(Source: Author's Fieldwork, 2024).

The results of the response of respondents to questionnaire to assess the vulnerability of four (4) categories of inhabitants with reference to the proximity to the river channel (Epie Creek) is presented in Table 2.2. It shows the total number of respondents are 857, about 69% of the respondents lives close to the channel (Epie Creek) while only about 31% were located far from the channel.

Table 3.2: Location of Respondents at Distance to the Epie Creek.

Proximity	Very Close	Close	Far	Very Far	Total
No. of Respondents	243	351	143	120	857
% Response	28.3	41.0	16.7	14.0	100

Results of assessment of Peoples' opinions on the degree of occurrence of flood in the area were sampled and results are presented in Table 3.3 It reveals that about 75% of inhabitants of the area who lives close to the river channel reported to experiencing flooding '*very often*' while only about 25% of inhabitants who lives far from the river channel reported that flooding in their area occurs '*very often*'. Again, those who reported to experience flooding '*often*'; about 64% lives close while 35% lives far from the channel.

Table 3.3: Proximity and Flood Frequency Around Buildings Along Epie Creek.

Proximity to Channel	No. of Respondents (%)	Very often (%)	Often (%)	Not too Often (%)	Cannot Explain (%)
Very Close	243 (28.30%)	69 (33.17%)	102 (27.13%)	41 (25.32%)	31 (27.93%)
Close	351 (41.00%)	87 (41.83%)	177 (47.07%)	61 (37.65%)	26 (23.42%)
Far	143 (16.70%)	34 (16.35%)	54 (14.36%)	28 (17.28%)	27 (24.32%)
Very Far	120 (14.00%)	18 (8.7%)	43 (11.44%)	132 (19.28%)	27 (24.32%)
Total	857	208	376	162	111
%	100	24.28%	42.87%	18.90%	12.95%

Source: Authors' Fieldwork (2024).

Proximity and extent of flood water around buildings within the study area was also assessed from respondents' opinions and the results are presented in Table 3.4. It shows that out of the 34.19% of those who reported that flood waters surrounds the whole premises (buildings); about 65% lives very close and close to the river channel (Epie Creek), while only 35% lives far and very far from the Creek. For those who reported that flood waters covers two-third of their premises; 60% of them live close and very close to the channel while the remaining 35% lives far and very far from the channel.

Table 3.4: Proximity and Flood Extent around Buildings along Epie Creek

Proximity to Channel	No. of Respondents (%)	Surrounds whole Building (%)	Surrounds 2/3 Building (%)	Surrounds 1/2 Building (%)	Surrounds only small portion (%)
Very Close	243 (28.30%)	83 (28.33%)	74 (25.0%)	48 (30.97%)	38 (33.63%)
Close	351 (41.00%)	109 (37.20%)	135 (45.61%)	70 (45.16%)	37 (32.74%)
Far	143 (16.70%)	53 (18.09%)	50 (16.89%)	21 (13.55%)	19 (16.81%)
Very Far	120 (14.00%)	48 (16.38%)	37 (12.50%)	16 (10.32%)	19 (16.81%)
Total	857	293	296	155	113
%	100	34.19%	34.54%	18.09%	13.18%

Source: Authors' Fieldwork (2024).

The results of the assessment of proximity and flood duration around buildings are presented in Table 3.5. It shows that out of the 38.86% of those who reported that flood water lasts for a period between one to two months; more than 80% of them live very close and close to the channel (Epie Creek) while, less than 20% live far and very far from the channel. For those who reported that flood water resides within a space of one month; more than 70% live very close and close to the channel while, less than 30% live far and very far from the channel.

Table 3.5: Proximity and Flood Duration around Buildings along Epie Creek

Proximity to Channel	No. of Respondents (%)	1-2 Month (%)	Within 1-Month (%)	Less than 1-Month (%)	Unknown (%)
Very Close	243 (28.30%)	105 (31.53%)	84 (33.20%)	40 (20.10%)	14 (19.44%)
Close	351 (41.00%)	166 (49.85%)	94 (37.15%)	63 (31.66%)	28 (38.89%)

Far	143 (16.70%)	32 (9.61%)	47 (18.58%)	45 (22.61%)	19 (26.39%)
Very Far	120 (14.00%)	30 (9.01%)	28 (11.07%)	51 (25.63%)	11 (15.28%)
Total	857	333	253	199	72
%	100	38.86%	29.52%	23.22%	8.40%

Source: Authors' Fieldwork (2024).

3.2 Discussion

Vulnerability of the inhabitants of the area.

i). Flood height/Elevation of the Area: two factors were considered which include; *flood height reached during 2022 flood event and the elevation of the area above mean sea level (MSL)* as shown in table 3.1. Results showed that the flood height ranges between 1.6m and 3.2m. Thus, areas within Ekeki, Amarata and Onopa were found to be more at risk of flooding followed by areas within Opolo to Biogbolo due to the relatively higher level of flood water than other areas (See Figure 2.1). On the elevation, results show that the area stands between 9m and 12m above MSL where as areas within Yenezue-Epie-Okaka and Etegwe-Okutukutu are found to be relatively lower (9.5m) than areas within Igbogene-Yenegwe (13m), Akenfa-Agudama (12m) and OpoloBiogbolo (11.5m) above MSL. But on the whole, the elevation of the area has been shown to decrease downstream from Igbogene to Onopa as shown in figure 3.2. The results of the study have shown that elevation above mean sea level is a major factor that exposed the communities along Epie Creek to flooding. This is because, the areas with higher record of flood height depicts areas with lower elevation above MSL.

The results of the correlation analysis showed a positive relationship ($r_{xy} = 0.098$) between the two sets of variables X and Y. A test of significance relationship using the t-test ($t_{cal} = r\sqrt{n-2}/1-r$) showed a no significant correlation between the two sets of variables (X, Y). This result further showed that the elevation of the area does not decrease or increase down /up the stream but alternates. This can be confirmed from the figure 3.2 where, the surface elevation of the area was seen to decrease from Igbogene to Etegwe but elevation starts to rise from Opolo and drops back within Yenezue-Epie/Okaka. The same scenario was observed for the data on the height of flood water on buildings where, the flood height was found to be relatively constant but drops within Etegwe/Okutukutu area but increases within Opolo but drops again within Yenezuegene to Okaka area. This further implies that, the level of flood (height) in the area is not directly determined by the elevation of the area above MSL. This means that the vulnerability to flooding of the area (in terms of flood height) is not directly caused by the low surface elevation with reference to MSL but other intervening variables may be responsible. Thus, while both variables

can influence the vulnerability of inhabitants of the area to flooding, one may not directly be the cause to the other.

ii) Dimension of flood waters around buildings located at distance to Epie Creek.

The vulnerability to flooding of communities along Epie Creek was also measured in terms of the dimension of flood waters usually found around residence of inhabitants of the area. Thus, the frequency of occurrence, the extent of spread and the duration (resident period) of flood waters around dwellings of inhabitants were assessed. Hence, peoples' opinion were sampled using well-structured questionnaire to assess the vulnerability of four (4) categories of inhabitants with reference to the proximity to the river channel (Epie Creek) namely, those whose dwellings are located *very close*, *close*, *far*, and *very far* from the channel. Table 2.2 shows the number of respondents (857) used for the analyses and their location with reference to the river channel. Results from Table 3.2 show that about 69% of the respondents' lives close to the channel while only about 31% were located far from the channel. This shows that greater percentage of the inhabitants of the area choose to live closer to the river channel owing to numerous benefits that may be derived from the source of water as suggested in Umeuduji (2017).

Flood Frequency within and around Buildings

Peoples' opinions on the degree of occurrence of flood in the area were sampled and results are presented in Table 3.3. From the responses; about 75% of inhabitants of the area who lives close to the river channel reported to experiencing flooding '*very often*' while only about 25% of inhabitants who lives far from the river channel reported that flooding in their area occurs '*very often*'. Again, those who reported to experience flooding '*often*'; about 64% lives close while 35% lives far from the channel. Meanwhile, for those who reported to be experiencing flooding '*not too often*'; 63% of them lives close and very close while about 37% of those who lives far reported that they experience flood not too often. Lastly, of the 13% of those who cannot explain the flood situation in the area, 51% lives close and very close while about 49% lives far and very far from the channel. Therefore, it is expedient to note that, proximity to the channel is a major factor that exposes the inhabitants of Epie Creek to flooding where, people whose building are located closer to the channel (Epie Creek) are expected to be more at risk of flooding than those living far. See Table 3.3.

Proximity and Flood Extent around Buildings.

This was measured in terms of coverage of flood waters around premises. The Table 3.4 showed that out of the 34.19% of those who reported that flood waters surrounds the whole premises (buildings); about 65% lives very close and close to the river channel, while only 35% lives far and very far from the channel. For those who reported that flood waters covers two-third of their

premises; 60% of them live close and very close to the channel while the remaining 35% lives far and very far from the channel. Again, for those who reported that flood water covers half of their premises, more than 75% of them live very close and close to the channel while only less than 25% of them live far and very far from the channel. Also, for those who reported that flood water covers only a small portion of their surroundings; more than 60% lives very close and close to the channel while less than 30% lives very far and far from the channel. This scenario indicates that although, there is variations in the spread of flood waters even amongst those who live close to the river channel; the results have shown that proximity to the channel is a major determinant that exposes the inhabitants of the area to flooding. Thus, those whose surroundings are located close to the channel are expected to be more at risk of flooding with regards to the spread of flood waters within their surroundings than those whose buildings are located far from the river channel.

Proximity and Flood Duration around Buildings

The duration of flood waters in terms of the resident period of water within the premises of inhabitants along the Epie Creek has been assessed from opinions of residents with reference to their location with distance from the channel. Thus, out of the 38.86% of those who reported that flood water lasts for a period between one to two months; more than 80% of them live very close and close to the channel while, less than 20% live far and very far from the channel. For those who reported that flood water resides within a space of one month; again, more than 70% live very close and close to the channel while, less than 30% live far and very far from the channel. Also, for those who reported that flood water resides for a period of less than one month; about 52% of them live close and very close to the channel while, about 40% lives far and very far from the channel. Also, out of about 8.4% of those who reported that the water resident period is not well known; about 59% live very close and close to the channel while, about 41% live far and very far from the channel. With the results presented in table 3.5, it is imperative to state that proximity to Epie Creek is another factor that contributes to the flood vulnerability of the people living in the area.

4.0 CONCLUSION AND RECOMMENDATIONS

4.1 Conclusion

The results of the study on the vulnerability to flooding of communities along Epie Creek has shown that though, the area is generally prone to flooding, but the elevation above MSL has been found to contribute less to the inhabitants exposure to flooding. Instead, the peoples' *proximity* to the channel has been identified as a key factor that exposes the people to flooding. Thus, since vulnerability is contextual, the results of the study have shown that people whose buildings are located close to the Epie channel are more exposed to flooding than those whose dwellings are located far from the channel.

4.2 Recommendations.

Based on the findings, the study recommends the relocation of inhabitants living very close to the channel. This will not only reduce level of casualties during flood events but would enable the proper planning of the environment such as the canalization of the Epie Creek.

REFERENCES

- Adelekan, I.O. (2010). Vulnerability of poor urban coastal communities to flooding in Lagos, state, Nigeria. *A Journal of Environment and urbanization*, vol. 22(2), 1-18.
- Cardona, O.D., Van Aalst, M.K., Birkmann, J., Fordham, M., McGregor, G., Perez, R., Pulwarty, R.S., Schipper, E.L.F., & Sinh B.T., (2012). Determination of risk, exposure and vulnerability. *A special report of the working group I and II of the IPCC, Cambridge, U.K and New York, NY, U.S.A*, pp 65-108.
- Collins, C.C., (2014). Evaluation of natural drainage flow pattern necessary for flood control using digital topographic information: A case study of Bayelsa state. *An international journal of environmental, Chemical, ecological and Geophysical Engineering*, vol. 9(7), 2014.
- Digha, O.N., Chima, G.N. & Obiene., E.A. (2009). The causes and problems of water pollution in Kolo Creek in Ogbia L.G.A of Bayelsa State, Central Niger Delta Region, Nigeria. *An international Journal of Environmental Science, Volume 5, Number 1, 2009*.
- Efobi, K. & Anierobi, C., (2013). Impact of flooding on riverine communities. The Experience of the Omambala area in Anambara state, Nigeria. *A journal of Economic and Sustainable Development*, vol. 4 (18).
- Izonfuo, L.W.A, and Bariweni, P.A. (2001) The effect of urban runoff water and human activities on some physico-chemical parameters of the Epie Creek in the Niger Delta. *Journal of Applied Science, Environment and Management*, Vol. 5(1), 47-55.
- Lungren, L., & Jonsson, A.C., (2012). Assessment of social vulnerability: a literature review of vulnerability related to climate change and natural hazards. www.diva.portal.org
- Kelman, I., (2007). Understanding vulnerability to understand disaster. Panel contribution to the Population-Environment Research Network Cyberseminar on Population and natural Hazards (November, 2007). www.populationenvironmentresearch.org/seminar.
- Kenji, T., Tadaihiro, M., Teruko, S., Teruki, F., Kami, S., & Saburo, I (2004). Factors determining residents' preparedness for floods in modern megapolises: the case of the Tokai flood disaster in Japan. *A journal of Risk Research*, vol. , issue 8-9 (2004).

- Liao, K. (2012). A theory on urban resilience to floods: a basis for alternative planning and practice. A journal of ecology and Society, vol. 17(4), 2012.*
- Proag, V., (2012). The concept of vulnerability and resilience. 4th International conference on building resilience, 8-10 September, 2014. Elsevier B.V publishers
[@www.elsevier.com/locate/procedia](http://www.elsevier.com/locate/procedia).
- Umeuduji, J. E. (2017) An Introduction to the Science of Landforms. *Jodogs and Aossociates, Mina. ISBN: 978-34122-6-4.*